


# RIC with S-receiver

## 15/10E/10/6E/6/4E/4



Fitting range



Minimal to severe hearing losses

Key features	15	10E	10	6E	6	4E	4
Processing channels	15	10	10	4	4	4	4
Automatic Adaptive Directionality	15	10	6	Broadband	Broadband	Broadband	Omni/Front
Acoustic Situation Technology	9 (Linked)	5 (Linked)	3	1	1	1	1
Adaptive fast slow compression	•/Linked	•/Linked	•/Linked	•	Classic	Classic	Classic
Programs	5	4	3	3	3	3	3
Push button*	•	•	•	•	•	•	•
Standard Noise Reduction	•	•	•	•	•	Minimal	Minimal
Zen	Linked	Linked	Linked	•	•	•	
Wireless CROS compatible	•	•	•	•	•	•	
Linear frequency transposition	•	•	•	•			
Ambient Noise Reduction	•	•	•	•			
Impulse Noise Rejection II	•	•	•				
Real Ear effect	•	•					
Linked Speech Enhancer II	•/Linked	•					
High frequency boost	•						
Wind noise control II	•						
<b>Accessories</b>							
App for iPhone, Android and new functionality	Via COM-DEX	Via COM-DEX	Via COM-DEX	Via COM-DEX	Via COM-DEX		
DEX accessories	•	•	•	•	•	RC-DEX/TV-DEX**	

\*Programmable: Volumen control II, program shift or a combination of the two \*\*Quick match only

Protection Class IP58

Colours

- 021  
 Warm Beige
- 081  
 Tan Silk
- 072  
 Winter Silver
- 073  
 Titan Grey
- 074  
 Midnight Black

# RIC with S-receiver


## 15/10E/10/6E/6/4E/4

### Technical data


	EAR SIMULATOR IEC 60118-0:1983 + A1:1994		2CC COUPLER IEC 60118-0:2015, ANSI S3.22-2014	
OSPL90	1600 Hz	110	101	dB SPL
	Peak	118	107	dB SPL
	Average	110	102	dB SPL
Acoustic output (Input 60 dB SPL)	1600 Hz	95	86	dB SPL
	Peak	103	92	dB SPL
	Average	92	86	dB SPL
Full-on gain (Input 50 dB SPL)	1600 Hz	58	49	dB
	Peak	63	52	dB
	Average	57	50	dB
Telecoil output (Input 31.6 mA/m)	1600 Hz	95	86	dB SPL
	Peak	103	92	dB SPL
	Average	92	86	dB SPL
Acoustic frequency range		100 - 10000	100 - 10000	Hz
Harmonic distortion (Input 70 dB SPL)	500 Hz	<2	<2	%
	800 Hz	<2	<2	%
	1600 Hz	<2	<2	%
Equivalent input noise		23	23	dB SPL
Battery current (stand by)		0.96	0.96	mA
Battery current		0.98	1.00	mA
Battery life (Type 312 Zn-Air, 170 mAh)		175	170	h
Mobile phone immunity (IEC 60118-13:2016, ANSI C63.19:2011)		IRIL: -36/-18/-13 dB SPL	U-rating: M4/T4	

Typical data obtained through standard pure tone measurements. Hearing aid set to Reference Test Gain, unless stated otherwise. Measured using a standard ITE coupler without wax guard.


MAXIMUM OUTPUT - EAR SIMULATOR



MAXIMUM OUTPUT - 2CC COUPLER



OUTPUT - EAR SIMULATOR



OUTPUT - 2CC COUPLER

